



传动数据类型	
最大输入扭矩	43.8 Nm
最大输出扭矩	35 Nm
适配螺母尺寸	max SW15
传动效率	80%
齿轮级别	2
传动比	1

未注公差/Unfilled Tolerance							GB/T 1804-2000f / GB/T 1184-1996H				
线性尺寸/Linear size							角度尺寸/Angular size				
(mm)	0.5-6	6-30	30-120	120-400	400-1000	1000-2000	≤10	10-15	50-120	120-400	>400
m ±	0.1	0.2	0.3	0.5	0.8	1.2	1°	30'	20'	10'	5'
f ±	0.05	0.1	0.15	0.2	0.3						

制图/Draw	签名/Name	年月日/Date	比例/Scale	热处理/Heat treatment
审核/Checked	牛从杰	2023/3/2	1.5:1	
批准/Approved	姚登乾	2023/3/6	重量/Weight (kg) 0.529	材料/Material
	陈躯宁	2023/3/6	纸张/Format A3	表面涂层/Surface coating

图号/Drawing No.	版本/Rev.
65218500	A

描述/Description	数量/Quantity
B-52-18-50	1



上海晟灏自动化科技有限公司  
Shanghai Shenghao  
Automation Technology Co., Ltd

图号/Drawing No. 65218500  
版本/Rev. A  
描述/Description B-52-18-50  
数量/Quantity 1